

# Technical data sheet

## Clamp clip, triple, FT plastic pressure trough

Item number: 1162160



Suitable for all C profile rails with slot width 16–17 mm.  
Hot-dip galvanised steel clamp and bolt, polypropylene pressure trough, halogen-free, colour light grey RAL 7035.  
Version with welding and/or locknuts for use under difficult circumstances and for shake protection on request.



St

Steel

FT

Hot-dip galvanised

### Master data

|                                   |                         |
|-----------------------------------|-------------------------|
| Item number                       | 1162160                 |
| Description 1                     | Clamp clip              |
| Description 2                     | triple                  |
| Manufacturer                      | OBO                     |
| Dimension                         | 12-16mm                 |
| Material                          | Steel                   |
| Surface                           | Hot-dip galvanised      |
| Surface standard                  | DIN EN ISO 1461         |
| Smallest sales unit               | 50                      |
| Unit of quantity                  | Piece                   |
| Weight                            | 6.2 kg                  |
| Weight unit                       | kg/100 pc.              |
| CO Footprint (GWP) Cradle-to-Gate | 0,1151 kg COe / 1 Piece |


# Technical data sheet

## Clamp clip, triple, FT plastic pressure trough

Item number: 1162160



### Dimensions



|                  |        |
|------------------|--------|
| Dimension A      | 23 mm  |
| Dimension B      | 20 mm  |
| Dimension C      | 34 mm  |
| Dimension G (mm) | M6     |
| Dimension H      | 82 mm  |
| Dimension L      | 47 mm  |
| Dimension t      | 1.5 mm |
| Dimension x      | 5 mm   |

### Technical data

|                                                |                |
|------------------------------------------------|----------------|
| Number of cables/pipes                         | 3              |
| for rail with slot width (with interval), max. | 17 mm          |
| for rail with slot width (with interval), min. | 16 mm          |
| Halogen-free                                   | yes            |
| Max. Tightening torque                         | 3 Nm           |
| With plastic trough                            | yes            |
| With metal trough                              | no             |
| Mounting type                                  | Profile rail   |
| Impact-resistant                               | no             |
| Clamping range D, max.                         | 16 mm          |
| Clamping range D, min.                         | 12 mm          |
| Surface addition                               | hot galvanised |
| Material addition                              | Steel          |
| With counter-trough                            | no             |
| Material of trough                             | Plastic        |
| Material quality of trough                     | Polypropylene  |