

Technical data sheet

GKS GX 60 FS cable tray

Item number: 6480035



GKS 60 GX = perforated cable tray system with 60 mm side height
Magnetic shield insulation without cover 20 dB, with cover 50 dB.



St	Steel
FS	Strip galvanized

Master data

Item number	6480035
Description 1	Cable tray
Manufacturer	OBO
Dimension	60x400x3000
Colour	zinc
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	3
Unit of quantity	Metre
Weight	501.14 kg
Weight unit	kg/100 m


Technical data sheet

GKS GX 60 FS cable tray

Item number: 6480035



Dimensions



Length	3,000 mm
Width	400 mm
Height	60 mm
Plate thickness	1.2 mm
Dimension B	400 mm
Dimension D	80 mm
Dimension H	60 mm
Dimension L	3,000 mm

Technical data

Connector version	Without connectors
Mounting system fastening type	Floor Ceiling Wall
Walkable	no
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	238 cm ²
Usable cross-section	23800 mm ²
Rustproof steel, pickled	no
Side perforation	yes
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

Technical data sheet


GKS GX 60 FS cable tray

Item number: 6480035



Loads

Support spacing 1.0 m	1.9 kN/m
Support spacing 1.5 m	1.1 kN/m
Support spacing 2.0 m	0.8 kN/m
Support spacing 2.5 m	0.9 kN/m



Load diagram, cable tray, type GKS GX60

- 1 Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- 3 Rail bend in mm at permitted kN/m
- 4 Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width