

Technical data sheet

GKS GX 60 FT cable tray

Item number: 6483030



GKS 60 GX = perforated cable tray system with 60 mm side height
Magnetic shield insulation without cover 20 dB, with cover 50 dB.



St	Steel
FT	Hot-dip galvanised

Master data

Item number	6483030
Type	GKS GX 605 FT
Description 1	Cable tray
Description 2	perforated
Manufacturer	OBO
Dimension	60x50x3000
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	3
Unit of quantity	Metre
Weight	93.3 kg
Weight unit	kg/100 m


Technical data sheet

GKS GX 60 FT cable tray

Item number: 6483030



Dimensions



Length	3,000 mm
Width	50 mm
Height	60 mm
Plate thickness	0.6 mm

Technical data

Connector version	Without connectors
Mounting system fastening type	Floor Ceiling Wall
Maintain electrical functions	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	29 cm ²
Usable cross-section	2900 mm ²
ROHS-conformant	yes
Rustproof steel, pickled	no
Side perforation	yes
Wide-span version	no

Technical data sheet


GKS GX 60 FT cable tray

Item number: 6483030



Loads

Support spacing 1.0 m	1.2 kN/m
Support spacing 1.5 m	0.6 kN/m
Support spacing 2.0 m	0.5 kN/m
Support spacing 2.5 m	0.3 kN/m



Load diagram, cable tray, type GKS GX60

- 1 Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- 3 Rail bend in mm at permitted kN/m
- 4 Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width
- * From a 100 mm width checked with joint plate