

Technical data sheet

Cable tray GKS FL 60 FSKSW

Item number: 6487790



GKS 60 FL = unperforated cable tray system with 60 mm side height.



St Steel

PE50 PES50 - Polyester/epoxy

Master data

| | |
|---------------------|-------------------------|
| Item number | 6487790 |
| Type | GKS FL 615 FSKSW |
| Description 1 | Cable tray GKS |
| Description 2 | unperforated |
| Manufacturer | OBO |
| Dimension | 60x150x3000 |
| Colour | Jet black; RAL 9005 |
| Material | Steel |
| Surface | PES50 - Polyester/epoxy |
| Surface standard | |
| Smallest sales unit | 3 |
| Unit of quantity | Metre |
| Weight | 177.635 kg |
| Weight unit | kg/100 m |


Technical data sheet

Cable tray GKS FL 60 FSKSW

Item number: 6487790



Dimensions




| | |
|-----------------|----------|
| Dimension | 60x150 |
| Length | 3,000 mm |
| Width | 150 mm |
| Height | 57 mm |
| Plate thickness | 0.7 mm |
| Dimension W | 152 mm |

Technical data

| | |
|--------------------------------|----------------------|
| Connector version | Without connectors |
| Mounting system fastening type | Floor Ceiling Wall |
| Maintain electrical functions | no |
| Mounting perforation in base | no |
| NATO hole pattern | no |
| Usable cross-section | 88 cm ² |
| Usable cross-section | 8800 mm ² |
| Rustproof steel, pickled | no |
| Side perforation | no |
| Wide-span version | no |

Loads

| | |
|-----------------------------------|----------|
| Insertable support spacings, min. | 1.5 m |
| Insertable support spacings, max. | 2.5 m |
| Support spacing 1.5 m | 1.5 kN/m |
| Support spacing 2.0 m | 1 kN/m |
| Support spacing 2.5 m | 0.5 kN/m |



Load diagram, cable tray, type GKS FL60

- 1 Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- 3 Rail bend in mm at permitted kN/m
- 4 Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width