


Technical data sheet

Cable ladder LG 100, 3 m VS

Item no. 6487102



Cable ladder with perforated side rail of side height 100 mm with riveted C profile rungs, open in an upwards direction. Assignment of the rungs on both sides possible using U clamps.

Magnetic shield insulation without cover 10 dB, with cover 15 dB.




St	Steel
FT	Hot-dip galvanised

Master data

Item no.	6487102
Type	LG 1020 VS FT
Description 1	Cable ladder
Description 2	perforated
Dimension	100x200x3000
Material	Steel
Material symbol	St
Surface	Hot-dip galvanised
Surface to DIN	DIN EN ISO 1461
Surface symbol	FT
Smallest sales unit (VG)	3 m
Weight	479,93 kg/100 m

Technical data



Length	3.000,00 mm
Width	200,00 mm
Height	100,00 mm
Side height	100,00 mm
Rail thickness	2,00 mm
Usable cross-section	15.800,00 mm ²
Usable cross-section	158,00 cm ²
Rung distance	300,00 mm

Appr. load:

Support spacing 2.0 m	2,60 kN/m
Support spacing 2.5 m	1,70 kN/m
Support spacing 3.0 m	1,30 kN/m
Support spacing 4.0 m	0,50 kN/m