


Technical data sheet

Empty housing X 25

Item no. 2005544



Junction box for the connection of cables and lines indoors and in outdoor areas. Rectangular design without entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK08. Transparent cover with quick lock, sealable. Made from halogen-free and UV-resistant materials. Junction box according to DIN EN 60670. Impact resistance IK08 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.





PC Polycarbonate

Additional product text, instruction	The junction box is tested according to DIN EN 60670-1, VDE 0606-1:2014 (EN 60670-1:2005 + Cor.:2007 + Cor.:2010 + A1:2013) and DIN EN 60670-22, VDE 0606-22:2007 (EN 60670-22:2006).
Additional product text 1	The junction box fulfils the protection type test requirements to IP 67 according to DIN EN 60529, VDE0470-1:2014 (EN 60529/AC:2016).
Additional product text 2	The cover is made of a transparent material for better observation of the installations.

Master data

Item no.	2005544
Type	X25C LGR-TR
Description 1	Empty Enclosure
Description 2	with transparent lid
Dimension	286x202x125
Colour	Grey/transparent
Material	Polycarbonate
Material symbol	PC
Smallest sales unit (VG)	1 Piece
Weight	95,00 kg/100 pc.

Technical data



Length	286,00 mm
Width	202,00 mm
Height	126,00 mm
Clear internal dimensions	271x187x110 mm
Dimension LxWxH	286x202x126 mm
Extension option	☐
Cover fastening	Screwed
Shape	Rectangular
Suitable for outdoor use	☒
With cover	☒
Installation type	On cable tray
Mounting type	Surface-mounted
Protection rating	IP67
Protection rating	IP 67
Protection rating IK code	IK08
Protection class	II
max. permitted ambient temperature	-25,00 - 65,00 °C
Transparent lid	☒

Technical data sheet

Empty housing X 25

Item no. 2005544



Technical data

Weatherproof

